



### Overview

Model Name	APC Smart-UPS 1500VA LCD RM 2U 120V with Network Card
Includes	CD with software , Documentation CD , Installation guide , Rack Mounting support rails , USB cable
Standard Lead Time	Usually in Stock
Product Distribution	Anguilla , Antigua And Barbuda , Aruba , Bahamas , Barbados , Belize , Bermuda , Canada , Cayman Islands , Colombia , Costa Rica , Cuba , Dominican Republic , Ecuador , El Salvador , Guatemala , Haiti , Honduras , Jamaica , Mexico , Nicaragua , Panama , Puerto Rico , Trinidad And Tobago , United States , Venezuela , VIRGIN ISLANDS (UNITED STATES)

### Output

Output Power Capacity	1000 Watts / 1440 VA
Max Configurable Power (Watts)	1000 Watts / 1440 VA
Nominal Output Voltage	120V
Output Voltage Distortion	Less than 5%
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz
Output Frequency (sync to mains)	Line Interactive
Waveform Type	Sine wave
Output Connections	(6) NEMA 5-15R (Battery Backup)

### Input

Nominal Input Voltage	120V
Input Frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	NEMA 5-15P
Cord Length	8 feet (2.44 meters)
Input voltage range for main operations	82 - 144 V
Maximum Input Current	0 A
Input Breaker Capacity	0 A

### Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Included Battery Modules	0
Battery Slots Empty	0

Typical recharge time	3 hour(s)
Replacement Battery	APCRBC133 , CURK133-01-03
RBC Quantity	1

## Communications & Management

Interface Port(s)	RJ-45 10/100 Base-T , RJ-45 Serial , SmartSlot , USB
Available SmartSlot™ Interface Quantity	0
Pre-Installed SmartSlot™ Cards	AP9631
Control panel	Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Emergency Power Off (EPO)	Optional

## Surge Protection and Filtering

Surge energy rating	459 joules
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

## Physical

Maximum Height	3.5 inches (89.0 mm)
Maximum Width	17.0 inches (432.0 mm)
Maximum Depth	18.0 inches (457.0 mm)
Rack Height	2 U
Net Weight	63.2 lbs (28.67 kg)
Shipping Weight	70.41 lbs (31.93 kg)
Shipping Height	9.89 inches (251.0 mm)
Shipping Width	23.38 inches (594.0 mm)
Shipping Depth	23.75 inches (603.0 mm)
Master Carton Units	0.0
Master Carton Weight	0.0 lbs
Color	Black
Units per Pallet	8.0

## Environmental

Operating Environment	32 - 104 °F (0 - 40 °C)
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-10000 feet (0-3000 meters)
Storage Temperature	5 - 113 °F (-15 - 45 °C)
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-50000 feet (0-15000 meters)
Audible noise at 1 meter from surface of unit	46.000 dB
Online Thermal Dissipation	90.000 BTU/hr

## Conformance

Approvals	CSA , ENERGY STAR V1.0 (USA) , FCC Part 15 Class A , UL 1778
Standard warranty	3 years repair or replace (excluding battery) and 2 years for battery

## Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs
Battery Directive	Compliant

