

5000-DU-FSR - RUGGED INDUSTRIAL DESKTOP KEYBOARD (QUICKSHIP)



\$520.00 USD

Industrial desktop keyboard, w/ Built-in Mouse

- Environmentally Sealed to NEMA 4, 4X / IP65 specifications
 - ABS-Polycarbonate Sealed Plastic Case
- 116 Keys including 24 Function Keys, 26 Key numeric keypad
 - Built-in 3 button FingerTipMouse (Pointing Device)
 - “CLEAN KEY” disengages keys for easy cleaning
 - No room for bacteria and infection trap
 - Greater than 10 Million cycles expected life
 - Includes 10' cable with USB interface
 - Built-in Mounting Holes



GALLERY IMAGES



PRODUCT DESCRIPTION

The Stealth Computer model 5000-DU-FSR is a NEMA 4, 4X, IP65 rated keyboard enclosed in a rugged ABS polycarbonate case. It features 116-key functionality, including 24 function keys and a 26 Key numeric keypad. The 5000-DU-FSR also features a "CLEAN KEY" that disengages keys for easy cleaning and the keyboard is designed with no room for bacteria or infection traps. Its integrated 3 button FingerTipMouse (Pointing Device) makes the 5000-DU-FSR with a PS/2 or USB connection a total solution in one convenient package.

ADDITIONAL INFORMATION**Industrial Approvals**

NEMA 4, 4X / IP65 UL 60950, CE, FCC Class B

Key Switch

Material: Industrial Silicone Rubber

Life: Greater than 10 million cycles

Travel: 0.055" (1.4mm)

Actuation Force: 200g (+/- 30g) / 7.05oz (+/- 1.06oz)

Feedback: Tactile with mechanical snap

PS/2 Keyboard: 35mA @ 5V (from keyboard Port)

PS/2 Mouse: 5mA @ 5V (from mouse port)

Power

* PS2 Current ratings valid only when both keyboard and mouse are connected

USB Keyboard / Mouse: 40mA @ 5V from USB port

Temperature Range

Operating: -20C to +60C (-4F to +140F)

Storage: -40C to +70C (-40F to +158F)

Humidity

100% (when properly installed)

Shock

3x11 ms pulses of 50g on each of 3 axes

Vibration

Power Spectral Density: 0.04g/Hz, Frequency Range: 20Hz-2kHz,

Duration of Test per Axis: 3 hours

Dimensions

(W-D-H) 14.94" x 6.63" x 1.81" (379.5mm x 168.4mm x 45.9mm)

Cable

Design: 10 Feet (3.05 meters) Single 10' "Y-Split" Cable with PS/2 Connectors, or Single USB Cable

Compatibility

PS/2: All windows operating systems most Linux/Unix Systems,

USB: All windows operating systems, MAC OS and most

Linux/Unix Systems

Additional Options

Custom cable lengths, special connectors, custom enclosures etc

Other Languages Available - Contact us for more details,

Minimum quantities may apply.

Warranty

1 Year limited Warranty Standard

Model Numbers

5000-DU-FSR-PS/2 (PS/2 Interface)

5000-DU-FSR-USB (USB Interface)

Disclaimer

Note: Specifications are subject to change without notice.