

17" LCD MONITOR / KEYBOARD 2U RACK DRAWER WITH 8 & 16 PORT KVM (FR-2002-17-KVM)



\$2,915.00 USD

Model: FR-2002-17-KVM

- KVM with 8, 12, or 16 Ports (DB-15, or DVI)
- 17" Slim 2U Rack LCD / Keyboard / Mouse
 - Saves Expensive Rack Space!
- Easily Installs into 19" Rack Cabinets
 - Folds down to 2U, 3.5" high
 - Built-in Keyboard & Touch Pad
- Field selectable for USB and PS/2
- 17.0" Bright Active Display Area
 - Built-in lockable Slide Rails
- Optional 8, 16 & 32 port KVM, DC Power, Video Inputs



GALLERY IMAGES



PRODUCT DESCRIPTION

Manage your Rack Space with a Slim 2U All-In-One LCD/Keyboard & Mouse with 8, 12, or 16 Built-in KVM Ports

Manage and expand your data center cost efficiently with the Stealth 8 and 16 Port KVM series FlatRacks. Stealth's LCD products have been designed for easy installation into standard 19" rack cabinets. The high strength slide-rails have lockable fixed positions to prevent movement when typing. In its resting position the Stealth LCD monitor measure only 3.5 inches or 2U in height providing a significant cost savings by using less rack space.

Stealth's ultra-thin LCD monitors come equipped with built-in keyboard and a track pad mouse connecting to both USB and PS/2 interfaces. Standard units ship with a built-in 110/220VAC power supply. Optional DC Power inputs of +12, +24 and -48VDC are also available. Other FlatRack models are available with a range of LCD sizes, Widescreen, and various video inputs.

ADDITIONAL INFORMATION

Construction & Design	19" Rackmount steel chassis 2U , 3.5" or 88.9mm high Latching front panel w/ 2-point lock
Screen Size	17.0" (Diagonal)
Type	TFT Active Matrix Liquid Crystal
Aspect Ratio	4:3
Native Resolution	1280 x 1024 (Auto sync from 640 x 480 to 1280 x 1024)
Response Time	5ms Typical
Viewable Image Size	Horizontal: 13.3" / 337.9 mm, Vertical: 10.6" / 270.4 mm
Video Signal	RGB Analog 0.7V Peak to Peak
Video Input Connectors	VGA / HD15 (Standard) DVI-D (Optional)
Viewing Angle	80 (up), 80 (down), 80 (left), 80 (right)
Contrast Ratio	1000:1 (typical)
Luminance (Brightness)	250 cd/m2 typical at center (250 Nits)
Controls On-Screen Display	Brightness, Contrast, H/V Position, Color, Phase, Clock, Language, etc.
Input	Internal 100~240VAC, 50/60Hz Power Supply Power Consumption: Max. 48 Watts, Standby 5 Watts 104 Keys
Built-in Keyboard / Mouse	3 Button Glide Point PS/2 and USB Combo cables included Operating Relative Humidity (non condensing) 20-90% Operating Temperature: 0~50C (32~122F) Storage Temperature: -5~60C (-23~140F)
Environmental	Relative Humidity: 5% ~ 90%, non-condensing (Operating & Non-Operating) Shock: 10G acceleration (11ms duration) Vibration: 5~500Hz 1G RMS random vibration
Color	Black (standard)

Unit Weight

Unit Weight: 46.4 Lbs (21.1 kg)

Available Models

FR-2002-17-KVM8 - 17" LCD/Keyboard/Trackpad with 8-Port KVM (DB-15)

FR-2002-17-KVM16 - 17" LCD/Keyboard/Trackpad with 16-Port KVM (DB-15)

Additional Options

Resistive/Capacitive Touchscreen

12/24/48VDC Power supply

DVI-D, BNC, S-Video, RCA Inputs

Dimensions

19.0"(W) x 3.5"(H) x 18.9"(D) (482.6 x 89.0 x 480 mm)

Warranty

2 Year Parts & Labor