

19" WIDESCREEN LCD MONITOR / KEYBOARD 1U RACK DRAWER WITH 8, 12, & 16 PORT KVM (FR-1002-19W-KVM)



\$2,790.00 USD

Model: FR-1002-19W-KVM

- KVM with 8, 12, or 16 Ports (DB-15 or DVI)
- 19" Slim 1U Rack LCD / Keyboard / Mouse
 - Widescreen 1440 x 900 resolution
 - Saves Expensive Rack Space!
- Easily Installs into 19" Rack Cabinets
 - Folds down to 1U, 1.75" high
 - Built-in Keyboard & Touch Pad
 - Field selectable for USB and PS/2
 - Optional DC Power, Video Inputs



GALLERY IMAGES



PRODUCT DESCRIPTION

Manage your Rack Space with a Slim 1U All-In-One LCD/Keyboard with 8, 12, or 16 Built-in KVM Ports

Manage and expand your data center cost efficiently with the Stealth 8 and 16 Port KVM series FlatRacks. Stealth's LCD products have been designed for easy installation into standard 19" rack cabinets. The high strength slide-rails have lockable fixed positions to prevent movement when typing. In its resting position the Stealth LCD monitor measure only 1.75 inches or 1U in height providing a significant cost savings by using less rack space.

Stealth's ultra-thin LCD monitors come equipped with built-in keyboard and a touch pad mouse connecting to both USB and PS/2 interfaces. Standard units ship with a built-in 110/220VAC power supply. Optional DC Power inputs of 12V, 24V, 48V, 125V, and 250VDC are also available. Other FlatRack models are available with a range of LCD sizes, Widescreen, and various video inputs.

ADDITIONAL INFORMATION

Construction & Design	19" Rackmount steel chassis 1U , 1.75" or 44.5mm high
Screen Size	19.0" (Diagonal)
Type	LCD c/w LED Backlighting
Aspect Ratio	16:9
Native Resolution	1440 x 900 (Auto sync from 720 x 400 to 1440 x 900)
Pixel Pitch	0.283mm x 0.283mm
Response Time	5ms Typical
Viewable Image Size	Horizontal: 16.06" / 408 mm, Vertical: 10.03" / 255 mm
Video Signal	RGB Analog 0.7V Peak to Peak
Video Input Connectors	VGA / HD15 (Standard) DVI-D & HDMI (Optional)
Viewing Angle	80 (up), 80 (down), 80 (left), 80 (right)
Contrast Ratio	1000:1 (typical)
Luminance (Brightness)	250 cd/m2 typical at center (250 Nits)
Controls On-Screen Display	Brightness, Contrast, H/V Position, Color, Phase, Clock, Language, etc.
Input	Internal 100~240VAC, 50/60Hz Power Supply Power Consumption: Max. 25 Watts, Standby 4 Watts
Built-in Keyboard / Mouse	104 Keys 2 Button Touch Pad USB cable included
Environmental	Operating Relative Humidity (non condensing) 20-90% Storage Relative Humidity (non condensing) 5-90% Operating Temperature: 0~50C (32~122F) Storage Temperature: -5~60C (-23~140F) Shock: 10G acceleration (11ms duration) Vibration: 5~500Hz 1G RMS random vibration
Color	Black (standard)

Unit Weight

Unit Weight: 25lbs (11.5 Kgs)

Available Models

FR-1002-19W-KVM8 - 19" Widescreen LCD/Keyboard/Touchpad with 8-Port KVM (DB-15)

FR-1002-19W-KVM16 - 19" Widescreen LCD/Keyboard/Touchpad with 16-Port KVM (DB-15)

Additional Options

KVM (Cat6) version with 8, 16 or 32 inputs available

12/24/48VDC Power supply

S-Video + Composite (BNC) + Audio input

DVI-D or HDMI Input

Dimensions

19.0"(W) x 1.75"(H) x 22.8 "(D) (482.6mm x 44.5mm x 579.1 mm)

Warranty

2 Year Parts & Labor