

5000-RDC-FSR-USB - RACKMOUNT KEYBOARD



\$730.00 USD

1U Rugged Environmentally Sealed Rackmount industrial keyboard

- Slim 1.75" high (1U) Rugged Industrial Keyboard
 - Environmentally Sealed, NEMA 12, IP52
- 112 Keys, 20 Function Keys, 22 Key numeric keypad
- Built-in 3 button FingerTipMouse (Pointing Device)
 - Built-in 12" slide rails
- Greater than 10 Million cycles expected life
 - Includes 10' straight USB cable



PRODUCT DESCRIPTION

The Stealth.com model 5000-RDC-FSR is a rugged industrial grade 1U rackmount keyboard that is environmentally sealed meeting NEMA 12, IP52 specifications. The silicon rubber overlay consists of 112-keys, 20 function keys, separate 22-key Number pad and an integrated industrial pointing device / mouse. The 5000-RDC-FSR comes with built-in slide rails at no extra cost and easily fits into a 19" rack cabinet. Whether your application is for a data center, industrial environment or Military facility, we have a rack keyboard drawer to meet your demands. Units are available with a USB connector.

In addition to our Rackmount Keyboards we also offer a wide range of rugged industrial keyboards and pointing devices that are available in stainless steel, desktop, panel mount, rack mount, OEM / open-frame, kiosk/public access and with illuminated / backlit features. Our peripherals have been used in a multitude of applications including HMI, operator interface, shop floor, data acquisition, kiosks, medical carts, mobile mount, and outdoor use to name a few.

ADDITIONAL INFORMATION

Industrial Approvals	NEMA 12, IP52 UL/ULc 60950, CE, FCC Class 15, Part B
Key Switch	Material: Industrial Silicone Rubber Life: Greater than 10 million cycles Travel: 0.055" (1.4mm) Actuation Force: 200g (+/- 30g) / 7.05oz (+/- 1.06oz) Feedback: Tactile with mechanical snap PS/2 Keyboard: 35mA @ 5V (from keyboard Port) PS/2 Mouse: 5mA @ 5V (from mouse port)
Power	* PS2 Current ratings valid only when both keyboard and mouse are connected USB Keyboard / Mouse: 40mA @ 5V from USB port
Temperature Range	Operating: -20C to +60C (-4F to +140F) Storage: -40C to +70C (-40F to +158F)
Humidity	100%
Shock	3x11 ms pulses of 50g on each of 3 axes
Vibration	Power Spectral Density: 0.04g/Hz, Frequency Range: 20Hz-2kHz, Duration of Test per Axis: 3 hours
Slide Load Rating	130 Lbs/Pair
Dimensions	(W-D-H) 19" x 15" x 1.75" (482.6mm x 381mm x 44.5mm)
Weight	Unit: 12.5lbs (5.67kg)
Cable	Design: 10 Feet (3.05 meters) Single 10' "Y-Split" Cable with PS/2 Connectors, or Single USB Cable
Compatibility	PS/2: All windows operating systems most Linux/Unix Systems, USB: All windows operating systems, MAC OS and most Linux/Unix Systems
Warranty	1 Year limited Warranty Standard
Model Numbers	5000-RDC-FSR-USB (USB Interface)
Disclaimer	Note: Specifications are subject to change without notice.