

# **DISCONTINUED: SR-4500B - INDUSTRIAL 4U RACK COMPUTER / SERVER (6TH GEN)**



## Model: SR-4500B

- Feature Rich 19" Rack PC/Server
- Powerful Intel 6th Gen Core Processors
- 4U, Solid Steel Enclosure w/ Secure Front Door
  - ATX Mainboards with Expansion Slots
  - Multiple Drive Bays for Massive Storage
    - Various Power Supply Options
  - Optional half-length front chassis door
  - Also available with Passive Backplane
     & Single Board Computer Design
    - Optional Stealth HMI Software
    - Built to your Exact Specifications
      - 2 Year Warranty
- 8th Gen version (Windows 10 only) also available

Important - The model SR-4500 (6th Gen) is now end-of-life and has been discontinued, if you have a requirement please contact us for assistance.







#### **GALLERY IMAGES**







### PRODUCT DESCRIPTION

The Stealth model SR-4500B is a high performance Industrial 4U Rack Mount Computer / Server designed to work on a continuous 24/7 basis yet are priced to meet your budget. Stealth has carefully selected, tested and qualified the highest quality of components to ensure the utmost in total system performance, reliability and long operational life cycles.

The SR-4500B 4U Rack PC features multiple drive bays for mass storage capability, RAID, PCIe expansion slots and various power supply options. Stealth's Industrial 4U Rack PC is fully custom configurable to meet your exact specifications.

Stealth's popular 4U Rack Mount systems utilize the latest Intel processors designed to deliver the ultimate in computing power that you require to meet your business and application needs. Prior to shipping each and every system is put through Stealth's rigorous QA burn-in procedure that is documented and controlled through our ISO 9001 quality system.



## **ADDITIONAL INFORMATION**

Supporting Intel® 6th Generation Core™ i7, i5, i3 Processors /

Supports Intel® 14nm CPUs

Optional support for Intel Xeon processors

Optional support for AMD Processors including Opteron

Dual-Channel memory architecture

4 DDR4 Memory Sockets Supporting up to 64GB of RAM /

**Memory** Memory

Processor

Additional customized solutions which include Triple-Channel or

higher memory configurations available

Supports all SATA (Serial-ATA) I, II & III Hard Drives (1.5Gb/s,

3Gb/s and 6Gb/s)

Optional support for SAS (Serial Attached SCSI), SCSI or Solid

State Hard Drives (SSD)

**Internal Storage** Optional Onboard RAID configurations (0, 1, 5, 10), requires

multiple drives (Note: this option may require a PCle expansion

slot)

Optional Intel Smart Response Technology on supported

**Processors** 

Shock mounted Drive Cage

(3) 5.25" Open Bay (For use with 5.25" Optical Drives, internal

Hard Drives, etc.)

**Drive Bays** (1) 3.5" Open Bay (For use with 3.5" Drives including 1.44MB

Floppy, Zip, etc.)

(1) 3.5" Internal optional cage for use with internal drive storage

(no shock mount)

Customized solutions for hot swap / removable drive assemblies

(1) PCle 3.0 x16 (operates at x4 mode)

**Expansion Slot(s)** (4) PCle 3.0 x1

(1) PCIe 3.0 x16

DVDRW/CDRW Optical Drive offered standard (uses 1 x 5.25"

Bay)

Removable Storage

Optional support for all Standard 5.25" Optical Disk Drives

Optional DVDRW/Blu-Ray Burner

Optional Removable drive bay with Key locking (uses 5.25"

expansion bay)



Video

Integrated Graphics Processor with DVI-D, HDMI and VGA/HD15

ports

Onboard integrated video, max. shared memory of 1GB,

supports up to 3 displays simultaneously

Includes DVI-D (Digital Only), VGA / HD-15 and HDMI ports

DVI-D max. resolution 1920 x 1200 @ 60 Hz

VGA / HD15 max. resolution 1920 x 1200 @ 60 Hz

HDMI max. resolution 4096 x 2160 @ 24 Hz / 2560 x 1600 @ 60

Hz

Supports triple-display simultaneously

Audio Onboard 8-Channel High Definition Audio CODEC

TPM Module Optional TPM 2.0 (Trusted Platform Module), provides increased

hardware security.

Networking Onboard 10/100/1000Base-T Gigabit LAN, RJ-45

Optional support for Fiber, 10GB, Wireless and more

(4) USB 3.1 Gen 1 Ports (rear-mounted)

(2) USB 2.0 / 1.1 Ports (rear-mount)

(2) USB 2.0 / 1.1 ports (front-mount)

(1) RJ45 10/100/1000 BASE-T Gigabit LAN Port

**Ports** (3) Audio Jacks (Input, Output and MIC)

(2) PS/2 ports for Keyboard & Mouse

(1) VGA / HD-15 Video

(1) DVI-D (Digital Only)

(1) HDMI

100-240 VAC, 50Hz - 60Hz, 650W power supply (standard)

Meets 80PLUS Gold

Power Supply
Optional Redundant Power Supplies

Optional 12, 24, 48, 125 and more DC input available

Windows 10 (64-bit)

Windows 7 (32 and 64-bit)

Windows 8.1 (32 and 64-Bit)

**Operating Systems** Windows Server 2008

Windows Server 2012 R2

**Ubuntu Linux** 

Please contact us directly for any special requirements



Solid State Drives (SSD) SATA

Removable drive bays

SCSI interface and hard drives

SAS (Serial attached SCSI) Drives and controllers

**RAID** 

**Options** Slide Rails

**Cooling Fans** 

DC input power options

3rd Party I/O Cards including RS232, RS485

3rd Party Video or Acceleration Cards

Video capture or input cards

Contact us with any request for configuration

Dual front intake Cooling Fans Removable Front Intake Filter

Full-length latching/locking door

**Environmental** Operating Temperature: 0~50C (32~122F)

**Dimensions** 7.0" H x 19.0" W x 20.0" D (178mm x 482mm x 510mm)

Weight Approx. 40 lbs. depending on configuration

Warranty 2 Year limited Warranty, Standard

1 Year Extended Warranty available (see Configurator/Price List)

**Disclaimer** Note: Specifications are subject to change without notice.