

SR-4570 - INDUSTRIAL 4U RACK PC WITH 7" LCD MONITOR



4U Rack Mount PC / Server with 7.0" LCD Monitor and Built in Keyboard and Mouse

- Built-in 7" LCD Monitor
- Built-in 84-Key keyboard and 2-Button Trackball
 - Powerful Intel 6th Gen Core Processors
 - ATX Mainboards with Expansion Slots
 - Multiple Drive Bays for Massive Storage
- AC/DC Power Supplies w/ Redundant Options
 - Built to your Exact Specifications
 - 2 Year Warranty

(Important Notice: The SR-4570 model is now end of life and has been discontinued, please contact us if you have a requirement.)



GALLERY IMAGES



PRODUCT DESCRIPTION

The Stealth SR-4570 series rack server has a built-in 7 inch widescreen LCD ideal for performance or application monitoring. The chassis design accommodates high performance processors from both Intel and AMD along with removable SATA hard drives. Another outstanding feature delivered by Stealth is the full integrated slide-out keyboard and trackball. When not used the keyboard and pointing device slides neatly under the rack chassis saving valuable space and without the time consuming need to search for keyboard and mouse cables.

The SR-4570 is highly configurable to meet any of your needs. Available with many Motherboard options, Slot configurations, CPU Support and Memory support.

ADDITIONAL INFORMATION**Processor**

Supporting Intel® 6th Generation Core™ i7, i5, i3 Processors /
Supports Intel® 14nm CPUs
Optional support for Intel Xeon processors
Optional support for AMD Processors including Opteron

Memory

Dual-Channel memory architecture
4 DDR4 Memory Sockets Supporting up to 64GB of RAM /
Memory
Additional customized solutions which include Triple-Channel or
higher memory configurations available

Internal Storage

Supports all SATA (Serial-ATA) I, II & III Hard Drives (1.5Gb/s,
3Gb/s and 6Gb/s)
Optional support for SAS (Serial Attached SCSI), SCSI or Solid
State Hard Drives (SSD)
Optional Onboard RAID configurations (0, 1, 5, 10), requires
multiple drives (Note: this option may require a PCIe expansion
slot)
Optional Intel Smart Response Technology on supported
Processors

Drive Bays

(3) Removable Drive Cages Standard with Chassis for SATA
Connection

Expansion Slot(s)

Standard offering includes (1) PCIe 3.0/2.0 x16, (1) PCIe 3.0/2.0
x16 (operates at x4 max), (2) PCIe 3.0/2.0 x1 and (2) PCI
DVDRW/CDRW Optical Drive offered standard (uses 1 x 5.25"
Bay)

Removable Storage

Optional support for all Standard 5.25" Optical Disk Drives
Optional DVDRW/Blu-Ray Burner
Optional USB 1.44MB 3.5" Floppy Drive

Video

Onboard integrated video, max. shared memory of 1GB, supports up to 3 displays simultaneously
Includes DVI-D (Digital Only), VGA / HD-15 and HDMI ports
DVI-D max. resolution 1920 x 1200 @ 60 Hz
VGA / HD15 max. resolution 1920 x 1200 @ 60 Hz
HDMI max. resolution 4096 x 2160 @ 24 Hz / 2560 x 1600 @ 60 Hz
Optional PCIe Graphics Adapter, Multiple monitor support, Quad or higher Video Options available

Audio

Onboard 8-Channel High Definition Audio CODEC

LCD Monitor

7" TFT, 800 x 480 Native Resolution with a 5 button control panel
Display Colors: 262,144 colors
Patch VGA cable to connect Video Card Output to LCD (external wire)

Keyboard

Built-In 84-Key PS/2 Keyboard and 2-Button PS/2 Trackball Mouse mounted in pull-out drawer with 2 sliding latches to keep it closed when not in use

Networking

Onboard 10/100/1000Base-T Gigabit LAN, RJ-45
Optional support for Fiber, 10GB, Wireless and more

Ports

(2) USB 2.0 / 1.1 Ports (rear-mount)
(2) USB 3.0 / 2.0 Ports (rear-mounted)
(2) USB 2.0 / 1.1 ports (front-mount)
(1) USB 5Gb/s port, Type C (supports 3A power output)
(1) RJ45 10/100/1000 BASE-T Gigabit LAN Port
(3) Audio Jacks (Input, Output and MIC)
(2) PS/2 ports for Keyboard & Mouse
(1) VGA / HD-15 Video
(1) DVI-D (Digital Only)
(1) HDMI
(1) Optional onboard DB9 Serial / RS232

Power Supply

100-240 VAC, 50Hz - 60Hz, 650W power supply (standard)
Meets 80PLUS Platinum
Optional Redundant Power Supplies
Optional 12, 24, 48, 125 and more DC input available

Operating Systems

Windows 10 (64-bit)
Windows 7 (32 and 64-bit)
Windows 8.1 (32 and 64-Bit)
Windows XP (32-Bit and 64-Bit)
Windows Server 2008
Windows Server 2012 R2
Ubuntu Linux
Please contact us directly for any special requirements

Options

Solid State Drives (SSD) SATA
Removable drive bays
SCSI interface and hard drives
SAS (Serial attached SCSI) Drives and controllers
RAID
Slide Rails
DC input power options
3rd Party I/O Cards including RS232, RS485
3rd Party Video or Acceleration Cards
Video capture or input cards
Contact us with any request for configuration

Environmental

Operating Temperature: 0 - 45C (32 to 113 F)

Dimensions

7.0" H x 19.0" W x 20.5" D (178mm x 482mm x 520mm)

Weight

Approx. 50 lbs. depending on configuration

Warranty

2 Year limited Warranty, Standard
1 Year Extended Warranty available (see Configurator/Price List)

Disclaimer

Note: Specifications are subject to change without notice.