

## 77-DP-BL-USB - COMPACT, SMALL FOOTPRINT ILLUMINATED KEYBOARD (DISCONTINUED)



### ***Ultra Small Rugged Illuminated Keyboard***

- Environmentally Sealed to NEMA 4, 4X / IP65 specifications
  - Backlighting / Illumination
  - ABS-Polycarbonate Sealed Plastic Case
    - Ultra Small Footprint Design
    - 77 Keys, 12 Function Keys
    - Low Profile Keys for Easy Cleaning
- Optional "Mobile" enclosure w/ bottom mounting studs
  - USB connector

**The model 77-DP-BL-USB is now End-of-Life, if you have a requirement please contact us or see our current lineup of rugged keyboards & pointing devices.**



## **PRODUCT DESCRIPTION**

The Stealth Computer model 77-DP-BL have been designed for those mobile applications when a compact small-footprint keyboard will come in handy. The NEMA 4X/IP65-rated 77-DP-BL keyboard offers a large amount of functionality in an ultra-small package. The 77-DP-BL is also ultra-thin and compact unit, it measures only 0.9 inches in height for the standard and the optional Mobile version is 1.61 inches deep and features mounting holes in its case. For working in low-light situations, the 77-DP-BL keyboard even comes with backlit/illuminated keys. Like other keyboards in the Stealth Computer line, the 77-DP-BL feature sealed, industrial silicone rubber keypads, as well as robust ABS polycarbonate cases.

**ADDITIONAL INFORMATION**

<b>Industrial Approvals</b>	NEMA 4, 4X / IP65 UL 60950, CE, FCC Class B
<b>Key Switch</b>	Material: Industrial Silicone Rubber Life: Greater than 10 million cycles Travel: 0.055" (1.4mm) Actuation Force: 135g (+/- 30g), 4.76 oz. +/- 1.06 oz. Feedback: Tactile with mechanical snap
<b>Power</b>	Keyboard: 200mA@5V (from CPU Port)
<b>Temperature Range</b>	Operating: -40C to +70C (-40F to +158F) Storage: -40C to +90C (-40F to +194F)
<b>Humidity</b>	100% (when properly installed)
<b>Shock</b>	3x11 ms pulses of 50g on each of 3 axes
<b>Vibration</b>	Power Spectral Density: 0.04g/Hz, Frequency Range: 20Hz-2kHz, Duration of Test per Axis: 3 hours
<b>Backlighting / Illumination</b>	Red LEDs (On/Off)
<b>Dimensions</b>	Standard Version - 9.27" x 3.87" x 0.9" (235.5mm x 98.3mm x 22.9mm) Mobile version - 9.31" x 3.88" x 1.61" (236.5mm x 98.6mm x 40.9mm)
<b>Cable</b>	Length: 3 feet (0.91 meters) Design: Single Cable USB
<b>Compatibility</b>	USB: All Windows Operating systems, most Linux/Unix operating systems and Macintosh OS Custom cable lengths, special connectors, custom enclosures etc
<b>Additional Options</b>	Other Languages Available - Contact us for more details, Minimum quantities may apply.
<b>Warranty</b>	1 Year limited Warranty Standard
<b>Model Numbers</b>	77-DP-BL-USB (USB Interface) 77-DP-BL-M-USB (Mobile - USB Interface)
<b>Disclaimer</b>	Note: Specifications are subject to change without notice.