

## **911-86-SL-TP - SMALL FOOTPRINT KEYBOARD WITH BUILT-IN TOUCHPAD MOUSE (DISCONTINUED)**



### ***Sealed Illuminated Keyboard/Mouse***

- Environmentally Sealed to NEMA 4, 4X / IP65 specifications
  - Backlighting / Illumination
  - ABS-Polycarbonate Sealed Plastic Case
    - Small Foot Print Design
- 86 Keys, 12 Function Keys, Emergency Key, FN Key
  - Built-in Touchpad Mouse
- Greater than 10 Million cycles expected life
  - PS/2 or USB connectors

***(Important Notice: The 911-86-SL-TP model is now end of life and is replaced by the functional equivalent model 880-DP-TP-BL.)***





## **PRODUCT DESCRIPTION**

The Stealth Computer model 911-86-SL-TP offers both a rugged keyboard and rugged touchpad mouse in one compact package. It boasts a completely sealed and ruggedized construction that allows it to meet NEMA 4X / IP65 specifications. The 911-86-SL-TP's backlighting is available with Red LEDs and provides bright keyboard illumination. Additionally, the 911-86-SL-TP features a specially designed Emergency key that when pressed, sends a signal of Shift+F1 and lights up for 30 seconds. The 911-86-SL-TP is available with PS/2 or USB connectors.

**ADDITIONAL INFORMATION**

<b>Industrial Approvals</b>	NEMA 4, 4X / IP65 UL 60950, CE, FCC Class B
<b>Key Switch</b>	Material: Industrial Silicone Rubber Life: Greater than 10 million cycles Travel: 0.055" (1.4mm) Actuation Force: 200g (+/- 30g) / 7.05oz (+/- 1.06oz) Feedback: Tactile with mechanical snap
<b>Power</b>	PS/2 Keyboard: 200 mA @ 5V (from Keyboard Port) PS/2 Mouse: 10mA @ 5V (from mouse port) USB: 210 mA @ 5V (from USB port)
<b>Temperature Range</b>	Operating: -40C to +70C (-40F to +158F) Storage: -40C to +90C (-40F to +194F)
<b>Humidity</b>	100% (when properly installed)
<b>Shock</b>	3×11 ms pulses of 50g on each of 3 axes
<b>Vibration</b>	Power Spectral Density: 0.04g/Hz, Frequency Range: 20Hz-2kHz, Duration of Test per Axis: 3 hours
<b>Backlighting / Illumination</b>	Red LEDs (On/Off)
<b>Dimensions</b>	(W-H-D) 12.0" x 7.74" x 1.27" (304.8mm x 196.6mm x 32.3mm)
<b>Cable</b>	Design: 4 Feet (1.2 meters) Single 4' "Y-Split" Coiled Cable with PS/2 Connectors, or Single USB Cable
<b>Compatibility</b>	PS/2: All windows operating systems most Linux/Unix Systems, USB: All windows operating systems, MAC OS and most Linux/Unix Systems
<b>Additional Options</b>	Custom cable lengths, special connectors, custom enclosures etc Other Languages Available - Contact us for more details, Minimum quantities may apply.
<b>Warranty</b>	1 Year limited Warranty Standard
<b>Model Numbers</b>	911-86-SL-TP-PS/2 (PS/2 Interface) 911-86-SL-TP-USB (USB Interface)
<b>Disclaimer</b>	Note: Specifications are subject to change without notice.