

1000-PM-NI-PS/2 - NON-INCENDIVE PANELMOUNT KEYBOARD



Rugged Sealed Non-Incendive Keyboard

- Environmentally Sealed to NEMA 4, 4X / IP65 specifications when properly installed.
 - Panelmount Stainless Steel Case
 - Includes Bulkhead Connectors
- 104 Keys, 12 Function Keys, WIN KEY, Numeric Keypad
 - Greater than 10 Million cycles expected life
 - PS/2 connector

(If you have a requirement please contact us for availability.)



PRODUCT DESCRIPTION

The Stealth Computer manufactures a full line of non-incendive keyboards and pointing devices. Each unit is enclosed in a stainless steel case and carries a Factory Mutual approval of Class I, Division II.

These units do not require barriers and are ideal for harsh working conditions. All units ship with bulkhead cables.

ADDITIONAL INFORMATION**Industrial Approvals**

FM Approved for Class I, II, III
Division II, Groups: A, B, C, D
NEMA 4, 4X, IP65* when properly installed, UL/ULc 60950, CE,
FCC Class 15, Part B

* Proper instructions must be followed to create a water-tight seal (NEMA 4X / IP65)

Material: Industrial Silicone Rubber

Life: Greater than 10 million cycles

Key Switch

Travel: 0.060" (1.5mm)

Actuation Force: 5oz (130g)

Feedback: Tactile with mechanical snap

Power

Keyboard: 5V@10ma (from CPU Port)

Temperature Range

-40C to +90C (-40F to +194F)

Humidity

100% (when properly installed)

Shock

3×11 ms pulses of 50g on each of 3 axes

Vibration

Power Spectral Density: 0.04g/Hz, Frequency Range: 20Hz-2kHz,

Duration of Test per Axis: 3 hours

Dimensions

(W-H-D) 17.7" x 9.2" x 2.0" (449.6mm x 233.7mm x 50.8mm)

CUTPIT: 16.4" x 7.9" (416.56mm x 200.66mm)

Cable

Length: 10 feet (3.94 meters)

Design: "Y" PS/2 Cable

Compatibility

Compatible with all Windows Operating Systems

Warranty

1 Year limited Warranty Standard

Model Numbers

1000-PM-NI-PS/2 (PS/2 Interface)

Disclaimer

Note: Specifications are subject to change without notice.