

SK-108-TP-MEM-USB - RUGGED KEYBOARD




\$595.00 USD

Rugged Industrial Keyboard with Built-in Mouse

- Environmentally Sealed to NEMA 4, 4X / IP68 specifications
 - ABS-Polycarbonate Sealed Plastic Case
 - 108 Keys, 12 Function Keys
 - Flush Surface, no crevices found between the keys
 - Lock Key for easy cleaning
 - Built-in Touchpad Pointing Device
 - VESA Mounting
 - CE, FCC & RoHS
 - USB connector



GALLERY IMAGES



PRODUCT DESCRIPTION

The Stealth Computer model SK-108-TP-MEM-USB is an excellent solution for space saving needs. An ultra-thin and compact unit, it measures only 1.06 inches (27mm) in height, while featuring an integrated touchpad for fast and accurate cursor position, eliminating the need for an external mouse.

The SK-108-TP-MEM-USB features a FN + LOCK combination key to disable the entire keyboard for easy cleaning. The keyboard surface is flush with anti-microbial functionalities, the fonts printed on the film underneath will never fade, and is made of durable, scratch-proof polyester to withstand to most chemicals and liquids under the harshest environments.

The keyboard lacks the crevices found between the keys of a regular keyboard, which is protected against dust, dirt, grease and corrosive liquids to NEMA 4X / IP68, which means it can withstand directed hose water, disinfectants, environmental contaminants and heavy industrial use. Ideal for use in Industrial automation, pharmaceutical, oil and gas, food and beverage, clean or dirty manufacturing environments and warehouses.

Stealth's industrial keyboards and pointing devices are also available in stainless steel, desktop, panel mount, rack mount, open-frame, kiosk/public access and with illuminated / backlit features.

ADDITIONAL INFORMATION**Industrial Approvals**

CE, FCC & RoHS

IP68 waterproof

Key Switch

Actuation Force: 1.0N for key 13.0mm x 13.0mm (press point)

Material: Membrane

Travel: 0.45mm (0.01")

Approximate Life: 3 million operations

EMC Standard: It is compliance with the council IEC

61000-4-2:2008 IEC 61000-4-3:2006+A1:2007+A2:2010 IEC

61000-4-4:2004

Power

EMI: EN 55022: 2010

EMS: EN 55024:2010

Supply Voltage: +5V DC +/-5%

Current Rating: Approx. 30mA

Temperature Range

Operating: -20C to 50C (-4F to 122F)

Humidity

100% Humidity Resistant

Mounting

VESA Mount (75 x 75mm, 100 x 100mm)

Dimensions

(L x W x H) 396.0mm x 150.0mm x (12.0mm - 27.0mm)

Cable

Length: 6 feet (2.0m)

Compatibility

USB: All Windows Operating systems, most Linux/Unix operating systems and Macintosh OS

Warranty

1 Year limited Warranty Standard

Model Numbers

SK-108-TP-MEM-USB (USB interface)

Disclaimer

Note: Specifications are subject to change without notice.