

## 17" RUGGED DESKTOP INDUSTRIAL LCD MONITOR (TT-1706)



**\$2,545.00 USD**

***Model: TT-1706***

- 17" Rugged Metal Enclosed Industrial LCD Monitor
  - Resistive Touch Screen Standard
  - Supports VESA 100mm Mounting
    - 17.0" Active Display Area
  - Wide range DC input (9 - 36V DC)
  - Wide Operating Temp (-10C - +50C)
- UL 62368-1:2019 Ed.3 & CAN/CSA C22.2#62368-1:2019 Ed.3 Listed (for 100~240V AC & 9~36V DC inputs only)
- Ideal for use in industrial and commercial environments
  - 3 Year Warranty



## GALLERY IMAGES



## PRODUCT DESCRIPTION

Stealth's TT-1706 is a 17" Rugged Touch Screen Industrial LCD Monitor designed to deliver performance and reliability that is ideally suited for industrial and commercial environments.

This Industrial LCD Display can be configured with a resistive touch screen (standard) or a Capacitive Touchscreen (optional). Additional features include a wide ranging DC input (9 - 36V DC) with an external AC Power Adapter. An optional 43~160V DC power input is also available. An extended operating temperature of -10C - +50C (14F - 122F) and a 3-Year Warranty are also included.

The TT-1706 features rear VESA 100mm mounting allowing it to be connected to a wide-range of versatile mounting options such as Wall, Bench top, Pendant Arm and Ceiling mounts.

Prior to shipping, each and every display is put through Stealth's rigorous QA burn-in procedure that is documented and controlled through our ISO 9001 quality system and in compliance with being UL 62368-1:2019 Ed.3 & CAN/CSA C22.2#62368-1:2019 Ed.3 listed (for 100~240V AC & 9~36V DC inputs only).

In addition to our Rugged Desktop Displays, Stealth offers a wide range of LCD product offerings that include Panel mount, Rack mount and Open Frame designs available in up to 24" diagonal sizes.

**ADDITIONAL INFORMATION**

<b>Screen Size</b>	17.0" (Diagonal)
<b>Aspect Ratio</b>	5:4
<b>Native Resolution</b>	1280 x 1024 (Auto sync from 640 x 480 to 1280 x 1024)
<b>Pixel Pitch</b>	0.264mm x 0.264mm
<b>Response Time</b>	30ms (Typical)
<b>Type</b>	TFT Active Matrix Liquid Crystal
<b>Video Input Connectors</b>	DVI-I c/w DVI to VGA Adapter HDMI Displayport
<b>Viewing Angle</b>	170° / 160° (H / V) - (Viewing angle of LCD panel without touch)
<b>Contrast Ratio</b>	800:1 (typical)
<b>Luminance (Brightness)</b>	350 cd/m2 typical at center (350 Nits)
<b>Viewable Image Size</b>	Horizontal: 13.3" / 337.92 mm, Vertical: 10.6" / 270.34 mm
<b>Input</b>	DC Input: 9V - 36V DC AC Adapter is Removable AC Input: 100-240V, 50-60Hz, 1.5A
<b>Control Buttons (Rear mounted)</b>	Power, Left, Right, Menu
<b>Controls On-Screen Display</b>	Brightness, Contrast, Input Source, Color, Image Adjust, OSD Lockout
<b>LCD Mounting Options</b>	Rear VESA 100mm Mounting
<b>Environmental</b>	Storage Temperature: -30C - +85C (-22F - +185F) Operating Temperature: -10 to 50C (14 to 122 F) Operating: Relative Humidity 20% ~ 80% Storage Relative Humidity: 20% ~ 80%
<b>Panel Finish</b>	Black Powder Coated
<b>Unit Weight</b>	Shipping Weight: 18.0 Lbs (8.17Kg) Unit Weight: 12.5 Lbs (5.7Kg)

**Dimensions**

16.52" x 13.48" x 4.45" (419.73mm x 342.51mm x 112.95mm)  
Without Mounted AC Adapter: 16.52" x 13.48" x 3.04"  
(419.73mm x 342.51mm x 77.22mm)

CSA C22.2#62368-1:2019 Ed.3 (for 100~240V AC & 9~36V DC inputs only)

**Approvals**

UL 62368-1:2019 Ed.3 (for 100~240V AC & 9~36V DC inputs only)

RoHS

CE

FCC

**Available Models**

TT-1706-RT - Resisitive (USB and Serial/DB9)

TT-1706-RT-160V - Resisitive Touch & 43V - 160V DC

**Warranty**

3 Year Parts and Labor

**Disclaimer**

Note: Specifications are subject to change without notice.