

## 20" LCD MONITOR / KEYBOARD 1U RACK DRAWER WITH 8 & 16 PORT KVM (DISCONTINUED)



### **Model: FR-1001-20-KVM**

- KVM with 8 or 16 Ports (DB-15)
- 20" Slim 1U Rack LCD / Keyboard / Mouse
  - Saves Expensive Rack Space!
- Easily Installs into 19" Rack Cabinets
  - Folds down to 1U, 1.75" high
  - Built-in Keyboard & Touch Pad
- Field selectable for USB and PS/2
- 20.0" Bright Active Display Area
  - 1600 x 1200 resolution
  - Built-in lockable Slide Rails
- Optional DC Power, Video Inputs

**The model FR-1001-20-KVM is now End-of-Life, if you have a requirement please contact us or see our current lineup of 1U & 2U Rack LCD / Keyboard Drawers.**



## GALLERY IMAGES



## PRODUCT DESCRIPTION

### **Manage your Rack Space with a Slim 1U All-In-One LCD/Keyboard with 8 or 16 Built-in KVM Ports**

Manage and expand your data center cost efficiently with the Stealth 8 and 16 Port KVM series FlatRacks. Stealth's LCD products have been designed for easy installation into standard 19" rack cabinets. The high strength slide-rails have lockable fixed positions to prevent movement when typing. In its resting position the Stealth LCD monitor measure only 1.75 inches or 1U in height providing a significant cost savings by using less rack space.

Stealth's ultra-thin LCD monitors come equipped with built-in keyboard and a track pad mouse connecting to both USB and PS/2 interfaces. Standard units ship with a built-in 110/220VAC power supply. Optional DC Power inputs of +12, +24 and -48VDC are also available. Other FlatRack models are available with a range of LCD sizes, Widescreen, and various video inputs.

**ADDITIONAL INFORMATION**

<b>Construction &amp; Design</b>	19" Rackmount steel chassis 1U , 1.75" or 44.5mm high Latching front panel w/ 2-point lock
<b>Screen Size</b>	20.0" (Diagonal)
<b>Type</b>	TFT Active Matrix Liquid Crystal
<b>Aspect Ratio</b>	4:3
<b>Native Resolution</b>	1600 x 1200 (Auto sync from 640 x 480 to 1600 x 1200)
<b>Response Time</b>	1ms Typical
<b>Viewable Image Size</b>	Horizontal: 16.06" / 408 mm, Vertical: 12.04" / 306 mm
<b>Video Signal</b>	RGB Analog 0.7V Peak to Peak
<b>Video Input Connectors</b>	VGA / HD15 (Standard) DVI-D & HDMI (Optional)
<b>Viewing Angle</b>	80 (up), 80 (down), 80 (left), 80 (right)
<b>Contrast Ratio</b>	800:1 (typical)
<b>Luminance (Brightness)</b>	300 cd/m2 typical at center (300 Nits)
<b>Controls On-Screen Display</b>	Brightness, Contrast, H/V Position, Color, Phase, Clock, Language, etc.
<b>Input</b>	Internal 100~240VAC, 50/60Hz Power Supply Power Consumption: Max. 48 Watts, Standby 5 Watts
<b>Built-in Keyboard / Mouse</b>	104 Keys 2 Button Touch Pad PS/2 and USB Combo cables included
<b>Environmental</b>	Operating Relative Humidity (non condensing) 20-90% Storage Relative Humidity (non condensing) 5-90% Operating Temperature: 0~50C (32~122F) Storage Temperature: -5~60C (-23~140F) Shock: 10G acceleration (11ms duration) Vibration: 5~500Hz 1G RMS random vibration
<b>Color</b>	Black (standard)
<b>Unit Weight</b>	Unit Weight: 44lbs (20.0 Kgs)

**Available Models**

FR-1001-20-KVM8 - 20" LCD/Keyboard/Trackpad with 8-Port KVM (DB-15)

FR-1001-20-KVM16 - 20" LCD/Keyboard/Trackpad with 16-Port KVM (DB-15)

**Additional Options**

KVM (Cat6) version with 8, 16 or 32 inputs available

12/24/48VDC Power supply

DVI-D, BNC, S-Video, RCA Inputs

**Dimensions**

19.0"(W) x 1.75"(H) x 25.6"(D) (482.6mm x 44.5mm x 650 mm)

**Warranty**

2 Year Parts & Labor