

20" LCD MONITOR / KEYBOARD 1U RACK DRAWER WITH 8, 16 & 32 PORT CAT6 KVM (DISCONTINUED)



\$2,595.00 USD


Model: FR-1001-20-KVM-Cat6

- Cat6 KVM with 8, 16 and 32 Ports
- RJ45 Interface with USB or PS/2 Dongles
- 20" Slim 1U Rack LCD / Keyboard / Mouse
- Control multiple systems from one LCD up to 120 ft or 40m away
- 8/16/32 Keyboard/Video/Mouse Inputs
- Easily Installs into 19" Rack Cabinets
 - Folds down to 1U, 1.75" high
- Field selectable for USB and PS/2
 - 1600 x 1200 resolution
- Built-in lockable Slide Rails
- Optional DC Power, Video Inputs

The model FR-1001-20-KVM-Cat6 is now End-of-Life, if you have a requirement please contact us or see our current lineup of 1U & 2U Rack LCD / Keyboard Drawers.



GALLERY IMAGES



Close up of the Rear View of Cat-6 KVM showing Qty 8 RJ45 interface Ports



Close up of the Rear View of Cat-6 KVM showing Qty 16 RJ45 interface Ports



Close up of the Rear View of Cat-6 KVM showing Qty 32 RJ45 interface Ports

PRODUCT DESCRIPTION

Manage your Rack Space with a Slim 1U All-In-One LCD/Keyboard with 8, 16 or 32 Built-in Cat6 KVM Ports with Standard RJ45 Interface Connection

The Stealth 8, 16 and 32 Port KVM series FlatRacks present an uncomplicated way for you to manage and expand your data center efficiently. PS/2 or USB combined with VGA or DVI connections are simply plugged into a small dongle that interfaces to a CAT5/CAT6 (RJ45 Connectors) cable. This allows each installation to a host system (Computer or Server) a maximum distance of up to 120 feet or 40 meters.

Stealth's LCD products have been designed for easy installation into standard 19" rack cabinets. The high strength slide-rails have lockable fixed positions to prevent movement when typing. In its resting position the Stealth LCD monitor measure only 1.75 inches or 1U in height providing a significant cost savings by using less rack space.

Stealth's ultra-thin LCD monitors come equipped with built-in keyboard and a track pad mouse connecting to both USB and PS/2 interfaces. Standard units ship with a built-in 110/220VAC power supply. Optional DC Power inputs of +12, +24 and -48VDC are also available. Other FlatRack models are available with a range of LCD sizes, Widescreen, and various video inputs.

ADDITIONAL INFORMATION

Construction & Design	19" Rackmount steel chassis 1U , 1.75" or 44.5mm high Latching front panel w/ 2-point lock
Screen Size	20.0" (Diagonal)
Type	TFT Active Matrix Liquid Crystal
Aspect Ratio	4:3
Native Resolution	1600 x 1200 (Auto sync from 640 x 480 to 1600 x 1200)
Response Time	1ms Typical
Viewable Image Size	Horizontal: 16.06" / 408 mm, Vertical: 12.04" / 306 mm
Video Signal	RGB Analog 0.7V Peak to Peak
Video Input Connectors	VGA / HD15 (Standard) DVI-D & HDMI (Optional)
Viewing Angle	80 (up), 80 (down), 80 (left), 80 (right)
Contrast Ratio	800:1 (typical)
Luminance (Brightness)	300 cd/m2 typical at center (300 Nits)
Controls On-Screen Display	Brightness, Contrast, H/V Position, Color, Phase, Clock, Language, etc.
Input	Internal 100~240VAC, 50/60Hz Power Supply Power Consumption: Max. 48 Watts, Standby 5 Watts 104 Keys
Built-in Keyboard / Mouse	2 Button Touch Pad PS/2 and USB Combo cables included Operating Relative Humidity (non condensing) 20-90% Storage Relative Humidity (non condensing) 5-90%
Environmental	Operating Temperature: 0~50C (32~122F) Storage Temperature: -5~60C (-23~140F) Shock: 10G acceleration (11ms duration) Vibration: 5~500Hz 1G RMS random vibration
Color	Black (standard)
Unit Weight	Unit Weight: 44lbs (20.0 Kgs)

Available Models

FR-1001-20-KVM8-Cat6 - 20" LCD/Keyboard/Trackpad with 8-Port Cat6 KVM

FR-1001-20-KVM16-Cat6 - 20" LCD/Keyboard/Trackpad with 16-Port Cat6 KVM

FR-1001-20-KVM32-Cat6 - 20" LCD/Keyboard/Trackpad with 32-Port Cat6 KVM

Additional Options

KVM version with 8 or 16 inputs available

12/24/48VDC Power supply

DVI-D, BNC, S-Video, RCA Inputs

Dimensions

19.0"(W) x 1.75"(H) x 25.6"(D) (482.6mm x 44.5mm x 650 mm)

Warranty

2 Year Parts & Labor