

21.5" ALL WEATHER LCD MONITOR, SUNLIGHT READABLE DISPLAY



\$2,895.00 USD

Model: SVM-2150W-RT-USB

- 21.5" Sunlight Readable Marine LCD Monitor
 - 1,000 Nits (Cd/m²) High Brightness
 - Widescreen, 16:9 Aspect Ratio
- Full HD 1080p, 1920 x 1080 Max Resolution
 - 9 to 36VDC Power Input
 - NEMA 4, IP65 Sealed Front Panel
- Operates in -10 to +50C temperatures
- VGA, DVI & Composite Video Inputs
 - Front Brightness Controls
 - Low Power LED Backlighting
- Touch Screen (Resistive Touch Standard)



GALLERY IMAGES



PRODUCT DESCRIPTION

The Stealth model SVM-2150W is a 21.5" Marine LCD Monitor that is sunlight readable and ideal for use in direct sunlight or high ambient light conditions. Typical applications would be for marine, industrial, security, kiosks, vehicles or outdoor displays as the LCD's front panel is environmentally sealed to NEMA 4/IP65.

Stealth's SVM-2150W features a front adjustable brightness control knob allowing for the LCD to be adjusted to low levels for night operation and a full 1000 nits for daytime bright sunlight conditions. Front controls also include night mode, video inputs, contrast etc. All Stealth monitors are available with touch screen capability or anti-glare glass for maximum protection.

The SVM-2150W operates from 9 to 36VDC which makes it ideal for marine and in vehicle applications. Stealth's 21.5" sunlight readable LCD features a wide range of video inputs that include dual VGA and DVI as well as 3 composite (NTSC) RCA input connectors. The 21.5" Marine display also features Full HD 1080p monitor with 1920 x 1080 maximum resolution (Widescreen, 16:9 Aspect Ratio).

Stealth's Marine / All Weather products also include Sealed Waterproof Computers, Sunlight Readable LCD Monitors, Weatherproof Keyboards and Mice.

ADDITIONAL INFORMATION

Screen Size	21.5" (Diagonal)
Aspect Ratio	16:9
Native Resolution	1920 x 1080 (Auto sync from 640 x 480 to 1920 x 1080)
Pixel Pitch	0.248mm x 0.248mm
Response Time	5ms Typical
Type	LCD c/w LED Backlighting
Video Input Connectors	2x Analog VGA / HD-15 2x Digital DVI 3x Composite
Touchscreen Interface	1x USB 2.0
Viewing Angle	170° / 160° (H / V)
Contrast Ratio	1000:1 (typical)
Luminance (Brightness)	1000 cd/m ² typical at center (1000 Nits) (adjustable)
Viewable Image Size	Horizontal: 18.76" / 476.64 mm, Vertical: 10.55" / 268.11 mm
Input	9V - 36V DC Input via Terminal Block Power Consumption: 40~45W typical (Note: an AC/DC Power Adapter is optional)
Control Buttons (Front mounted)	Brightness, Night Mode, Down, Menu, Up, Input, Power
LCD Mounting Options	Designed for Panel Mount (Flush Mount) VESA 100mm or 75mm mount (Note: VESA mounting not available if external AC/DC power adapter is used)
Environmental Rating	Standard Bezel: NEMA 4 / IP65 Front Panel (when properly installed) protection against windblown dust and rain, splashing water, and hose-directed water
Environmental	Operating Temperature: -10 to 50C (14 to 122 F) Storage Temperature: -20 to 70C (-20 to 158F)
Approvals	Meets ICE 60945 BV Marine and IACS-E10 RoHS

Available Models

SVM-2150W-RT-USB – Resistive Touch with USB Interface

Unit Weight

Unit Weight: 11.9 Pounds (5.39Kg)

Dimensions

Marine LCD Monitor: 20.7"(W) x 13.59"(H) x 2.2"(D) (525.8mm x 345.2mm x 56mm)

Warranty

1 Year Parts & Labor