

## 15" OPEN-FRAME LCD MONITOR




### **Model: SV-1501-OEM**

- 15" OEM/Open-Frame LCD Monitor
- Easily installs in kiosks, cabinets, walls, panels & consoles
- Resistive Touch Screen Standard c/w USB and Serial Connections
  - Optional Capacitive Touchscreen
    - Wide Viewing Angles
  - VGA & DVI-D video connectors
    - 1 Year Warranty

***(Important Notice: The SV-1501-OEM model is now end of life and is replaced by the functional equivalent model SV-1510-OEM.)***



## GALLERY IMAGES



## PRODUCT DESCRIPTION

Stealth's 15" Open Frame/OEM LCD design easily installs into your enclosure, cabinet, console, wall, kiosks or other applications. Mounting is straightforward with solid steel metal flanges located on all sides of the LCD each with mounting holes to secure the LCD in place. Our Open Frame LCD products are available with resistive/capacitive touchscreens or without a front overlay.

Stealth offers a wide range of LCD product offerings that include Panel mount, Rack mount and Open Frame designs as standard off-the-shelf products in 8.4" up to 26" diagonal sizes. Our LCD products are constructed from solid steel and will meet the demands of your application without breaking your budget.

**ADDITIONAL INFORMATION**

<b>Bezel Type</b>	Open-Frame
<b>Screen Size</b>	15.0" (Diagonal)
<b>Aspect Ratio</b>	4:3
<b>Native Resolution</b>	1024 x 768 (Auto sync from 640 x 480 to 1024 x 768)
<b>Horizontal Frequency</b>	57.3 KHz - 70 KHz, 67.5KHz typical
<b>Vertical Frequency</b>	57 Hz - 63 Hz, 60Hz typical (NTSC)
<b>Pixel Pitch</b>	0.297mm x 0.297mm
<b>Response Time</b>	5.7ms
<b>Type</b>	CCFL backlight Backlighting Life: 40,000 Hr Typical
<b>Video Input Connectors</b>	VGA / HD-15 DVI Compliant Digital HDCP (DVI-D)
<b>Viewing Angle</b>	140° / 125° (H / V) - (Viewing angle of LCD panel without touch)
<b>Contrast Ratio</b>	700:1 (typical)
<b>Luminance (Brightness)</b>	250 cd/m2 typical at center (250 Nits)
<b>Viewable Image Size</b>	Horizontal: 11.97" / 304.128 mm, Vertical: 8.98" / 228.096 mm
<b>Input</b>	12VDC input at LCD, Rear mounted AC power supply included, 100 - 240VAC (removable) Power Consumption: <45W (typical)
<b>Control Buttons (Rear mounted)</b>	Power Switch, Menu Key, Select (+, -), Auto
<b>Controls On-Screen Display</b>	Brightness, Contrast, Auto Adjust, Image Position, Image Adjust, Color Adjust, Display Mode, Language Select, OSM Lockout, OSM Time-out
<b>Environmental Rating</b>	OEM/Open-Frame chassis - not rated
<b>Environmental</b>	Operating Temperature: 0~50C (32~122F) Storage Temperature: 0~60C (32~140F) Relative Humidity: 10% ~ 90% non-condensing (Operating & Non-Operating)

<b>Panel Finish</b>	Black Baked Enamel (Standard) Stainless Steel - Brushed #304 (Optional)
<b>Unit Weight</b>	Unit Weight: 7 Lbs (3.2kg) without touchscreen Unit Weight: 8 Lbs (3.6kg) with touchscreen
<b>Dimensions</b>	For Dimensions please refer to the OEM Dimensional Drawing SV-1501-OEM - No touchscreen, LCD directly exposed SV-1501-OEM-RT - Resistive Touch with Serial/DB9 and USB Interface
<b>Available Models</b>	SV-1501-OEM-CT-SERIAL - Capacitive Touch with Serial/DB9 Interface SV-1501-OEM-CT-USB - Capacitive Touch Screen with USB interface
<b>Warranty</b>	1 Year Parts & Labor
<b>Disclaimer</b>	Note: Specifications are subject to change without notice.