

## 19" OPEN-FRAME LCD MONITOR (SV-1905-OEM)



**\$1,450.00 USD**

***Model: SV-1905-OEM***

- 19" OEM/Open-Frame LCD Display
  - Wide DC Input (9-36V DC)
- Wide operating temperature (-10C - +60C)
- Optional Resistive Touch Screen c/w USB and Serial Connections
  - Ideal for kiosks, cabinets, walls, panels, and consoles
  - 350 Nits of Brightness, Adjustable Controls
  - DVI-I, HDMI & DisplayPort video connectors
  - 3 Year Warranty



## GALLERY IMAGES



## PRODUCT DESCRIPTION

The SV-1905-OEM is Stealth's most recent introduction of an Open-Frame LCD Display designed specifically for cabinet, console, kiosk or other applications which do not require our Panel Mount version. This versatile display mounts from within the enclosure providing a wide array of options to ensure the end product meets your design needs. Built from solid cold rolled steel, it is designed for wide temperature operation and includes both an AC and DC input.

The SV-1905-OEM is backed with an impressive 3-year warranty. It delivers on performance! An optional resistive touch screen permits this product to replace traditional mice and allows users to directly interact with any system. View our other OEM/Open Frame LCD Displays if you need an alternate size.

As with all Stealth products, the unit is built in-house with our rigorous processes which both meet and exceed the ISO 9001 Quality Management System. Our attention to detail, multiple quality check points ensures the final product will arrive and operate the first time.

**ADDITIONAL INFORMATION**

<b>Bezel Type</b>	Open-Frame
<b>Screen Size</b>	19.0" (Diagonal)
<b>Aspect Ratio</b>	5:4
<b>Native Resolution</b>	1280 x 1024 (Auto sync from 640 x 480 to 1280 x 1024)
<b>Pixel Pitch</b>	0.294mm x 0.294mm
<b>Response Time</b>	10ms (Typical, On/Off)
<b>Type</b>	TFT Active Matrix Liquid Crystal
<b>Video Input Connectors</b>	DVI-I c/w DVI to VGA Adapter HDMI Displayport
<b>Viewing Angle</b>	170° / 160° (H / V) - (Viewing angle of LCD panel without touch)
<b>Contrast Ratio</b>	1000:1 (typical)
<b>Luminance (Brightness)</b>	350 cd/m2 typical at center (350 Nits)
<b>Viewable Image Size</b>	Horizontal: 14.81" / 376.32 mm, Vertical: 11.85" / 301.06 mm
<b>Input</b>	90 ~ 264V AC, 47~63Hz rear-mounted (removable) Power Supply DC Input (std.): 9V - 36V DC DC Input (opt.): 43V - 160V DC DC Input (opt.): 180V - 300V DC
<b>Control Buttons (Rear mounted)</b>	Power, Left, Right, Menu
<b>Controls On-Screen Display</b>	Brightness, Contrast, Input Source, Color, Image Adjust, OSD Lockout
<b>Environmental Rating</b>	N/A - not rated
<b>Environmental</b>	Operating Temperature: -10C - +60C (14F - 140F) Storage Temperature: -30C - +85C (-22F - +185F) Operating: Relative Humidity 20% ~ 80% Storage Relative Humidity: 20% ~ 80%
<b>Cooling</b>	Natural Convection (no fan)

<b>Panel Finish</b>	N/A - Open-Frame
<b>Unit Weight</b>	Unit Weight: 9.15 Lbs (4.14 Kg)* Shipping Weight: 14.85 Lbs (6.72 Kg)* * Weight may vary depending on configuration
<b>Dimensions</b>	17.8"(w) x 14.05"(h) x 3.45"(d) (452.12mm x 356.74mm x 87.64mm) NOTE: The depth does not include touch glass, add 12mm to depth for any touch option Without Mounted Power Supply: 17.8" (w) x 14.05" (h) x 2.11" (d) (452.12mm x 356.74mm x 53.72mm)
<b>Available Models</b>	SV-1905-OEM - No Touch Included SV-1905-OEM-160V - (43V - 160V DC) SV-1905-OEM-300V - (180V - 300V DC) SV-1905-OEM-RT - Resistive Touch (Serial/DB9 and USB) SV-1905-OEM-RT-160V - Resistive Touch & 43V - 160V DC SV-1905-OEM-RT-300V - Resistive Touch & 180V - 300V DC
<b>Warranty</b>	3 Year Parts and Labor
<b>Disclaimer</b>	Note: Specifications are subject to change without notice.