

19" OPEN-FRAME LCD MONITOR (DISCONTINUED)



Model: SV-1901-OEM

- 19" OEM/Open-Frame LCD Monitor
- Easily installs in kiosks, cabinets, walls, panels & consoles
 - Touch Screen Standard (Capacitive or Resistive)
 - Wide Viewing Angles
 - 250 Nits of Brightness, Adjustable Controls
 - VGA & DVI-D video connectors
 - cULus Listed
 - 1 Year Warranty

(Important Notice: The SV-1901-OEM model is now end of life and is replaced by the functional equivalent model SV-1905-OEM.)



GALLERY IMAGES



PRODUCT DESCRIPTION

Our Stealth model SV-1901-OEM is a 19" Open-Frame LCD Monitor designed to easily install into your enclosure, cabinet, console, wall, kiosks or other applications. Mounting is straightforward with solid steel metal flanges located on all sides of the LCD each with mounting holes to secure the LCD in place. Our OEM/Open Frame LCD products are available with resistive/capacitive touchscreens or without a front overlay.



Prior to shipping, each and every display is put through Stealth's rigorous QA burn-in procedure that is documented and controlled through our ISO 9001 quality system and in compliance with being cULus Listed, UL 60950-1 & CAN/CSA C22.2 No. 60950-1-07.

Stealth offers a wide range of LCD product offerings that include Panel mount, Rack mount and Open Frame designs as standard off-the-shelf products in 8.4" up to 24" diagonal sizes. Our LCD products are constructed from solid steel and will meet the demands of your application without breaking your budget.

ADDITIONAL INFORMATION

| | |
|---------------------------------------|---|
| Bezel Type | Open-Frame |
| Screen Size | 19.0" (Diagonal) |
| Aspect Ratio | 5:4 |
| Native Resolution | 1280 x 1024 (Auto sync from 640 x 480 to 1280 x 1024) |
| Horizontal Frequency | 30 kHz ~ 83 kHz |
| Vertical Frequency | 56 Hz ~ 75 Hz |
| Pixel Pitch | 0.294mm x 0.294mm |
| Response Time | 5ms Typical |
| Type | LCD c/w LED Backlighting |
| Video Input Connectors | VGA / HD-15 DVI Compliant Digital HDCP (DVI-D) |
| Viewing Angle | 170° / 160° (H / V) - (Viewing angle of LCD panel without touch) |
| Contrast Ratio | 1000:1 (typical) SmartContrast: 20,000,000:1 |
| Luminance (Brightness) | 250 cd/m2 typical at center (250 Nits) |
| Viewable Image Size | Horizontal: 14.81" / 376.32 mm, Vertical: 11.85" / 301.06 mm |
| Sync Signal | Separate Sync Sync on Green |
| Input | AC Input: 100-240V, 50-60Hz, 1.5A |
| Control Buttons (Rear mounted) | Smart Image, Down, Up, Menu/OK, Power ON/OFF |
| Controls On-Screen Display | Brightness, Contrast, Auto Adjust, Image Position, Image Adjust, Color Adjust, Display Mode, Language Select, OSM Lockout, OSM Time-out |
| Environmental Rating | OEM/Open-Frame chassis - not rated |
| Approvals | cULus Listed, UL 60950-1 & CAN/CSA C22.2 No. 60950-1-07 |
| Panel Finish | N/A - Open-Frame |

Unit Weight

Unit Weight: 9.15 Lbs (4.14 Kg)*

Shipping Weight: 14.85 Lbs (6.72 Kg)*

* Weight may vary depending on configuration

Dimensions

For Dimensions please refer to the OEM Dimensional Drawing

SV-1901-OEM - No protective glass, LCD directly exposed

SV-1901-OEM-RT - Resistive Touch with Serial/DB9 and USB Interfac

Available Models

SV-1901-OEM-CT-SERIAL - Capacitive Touch with Serial/DB9 Interface

SV-1901-OEM-CT-USB - Capacitive Touch Screen with USB interface

Warranty

1 Year Parts & Labor

1 Year Extended Warranty available (see Configurator/Price List)

Disclaimer

Note: Specifications are subject to change without notice.