

21.5" RACK MOUNT LCD MONITOR (SV-2155W-RM)



\$1,655.00 USD

Model: SV-2155W-RM

- 21.5" Wide Screen Rack Mount LCD
- Full 1080p HD resolution (1920 x 1080)
- VGA and HDMI Inputs (Optional DVI-D & Displayport)
 - Installs into (8U) of rack space
 - Easy snap in/out installation
- Optional Resistive Touch Screen
 - Front-access OSD Controls
 - 2 Year Warranty



GALLERY IMAGES



PRODUCT DESCRIPTION

The Stealth model SV-2155W-RM is our widescreen 21.5" Rack Mount LCD which installs into industry standard 19" EIA rack cabinets and enclosures in minutes. The SV-2155W-RM features a Full HD 1080p display (1920 x 1080 resolution), 16:9 Aspect Ratio with VGA and HDMI video inputs standard. Optional upgrades are available for VGA, DVI-D & HDMI or VGA, DisplayPort and dual HDMI video connections.

Both options include integrated Audio and dual 2 Watt Speakers. The 21.5" Rack display can also be configured with a Resistive Touch Screen and DC power options including 12V, 24V, 48V, 125V and 250V DC.

Stealth builds high quality Rackmount LCD monitors suited for industrial and commercial applications. We offer a wide range of LCD product offerings including Panel mount, Rack mount and Open Frame designs as standard off-the-shelf products in 8.4" up to 24" diagonal sizes. Our LCD products are constructed from solid steel and will meet the demands of your application without breaking your budget.

ADDITIONAL INFORMATION

Bezel Type	Rack Mount
Screen Size	21.5" (Diagonal)
Aspect Ratio	16:9
Native Resolution	1920 x 1080 (Auto sync from 640 x 480 to 1920 x 1080)
Pixel Pitch	0.248mm x 0.248mm
Response Time	5ms Typical
Type	LCD c/w LED Backlighting
Video Input Connectors	VGA/HD15 + DVI-D + HDMI inputs with Audio In/Out, Dual 2W Speakers (optional) VGA/HD15 + HDMI Inputs (standard) VGA/HD15 + 2x HDMI + DisplayPort with Audio In/Out, Dual 2W Speakers (optional)
Viewing Angle	170° / 160° (H / V) - (Viewing angle of LCD panel without touch)
Contrast Ratio	1000:1 (typical)
Luminance (Brightness)	250 cd/m2 typical at center (250 Nits)
Viewable Image Size	Horizontal: 18.77" / 476.64mm, Vertical: 10.56" / 268.11mm
Input	Optional: 12V, 24V, 48V, 125V and 250V DC with Terminal Block Power Consumption: 32W Max, Standby 4W 12VDC input at LCD, Rear mounted AC power supply included, AC Input: 100-240VAC 60/50 Hz @ 0.7A
Audio	Includes: 2 x 2W Speakers with 3.5mm Audio Jack Available only with DV4 and DP Options
Control Buttons (Rear mounted)	Smart Image, Down, Up, Menu/OK, Power ON/OFF
Controls On-Screen Display	Brightness, Contrast, Auto Adjust, Image Position, Image Adjust, Color Adjust, Display Mode, Language Select, OSM Lockout, OSM Time-out
Environmental Rating	N/A - not rated

Environmental

Non-Operating Altitude: 40,000 ft
Operating Altitude: 16,000 ft
Operating Humidity: 20~90%, non-condensing
Storage Humidity: 5~90%, non-condensing
Vibration: 10-300Hz 0.5G RMS random vibration
Operating Temperature: 0~55C (32~131F)
Storage Temperature: -20~60C (-4~140F)
Shock: 10G acceleration (11ms duration)

Panel Finish

Black Front Panel Finish

Unit Weight

Unit Weight: 19.4lbs / 8.8 kg

LCD Mounting Options

Rear VESA 100mm Mounting
Installs into (8U) of rack space
Designed to fit standard 19" EIA Racks

Dimensions

Rack Mount: 19.75"(W) x 13.89"(H) x 2.53"(D) (501.9mm x 353mm x 64.4mm)

SV-2155W-RM – Standard Model with VGA/HD15 and HDMI 1.4 inputs

SV-2155W-RM-DP – incl. VGA/HD15, HDMI 1.4, HDMI 2.0, DisplayPort 1.0 with Audio In/Out, Dual 2W Speakers

SV-2155W-RM-DV4 – incl. VGA/HD15, DVI-D, HDMI 1.4 with Audio In/Out, Dual 2W Speakers

Available Models

SV-2155W-RM Options:

-RTe-USB (Resistive Touchscreen with USB interface)

-12V (9~18VDC input)

-24V (18~36VDC input)

-48V (36~75VDC input)

-125V (66~160VDC input)

-250V (180~425VDC input)

Warranty

2 Year Parts & Labor

Disclaimer

Note: Specifications are subject to change without notice.