

17" SUNLIGHT READABLE LCD MONITOR (SV-1700LED-PM-HB) (DISCONTINUED)



Model: SV-1700LED-PM-HB

- 17.0" Sunlight Readable LCD Monitor
- 1,000 Nits (Cd/m²) HIGH BRIGHTNESS
 - LED Backlighting
- NEMA 4X / IP66 Sealed Front Panel Stainless Steel #304, brushed
 - Adjustable Brightness Controls
- Touchscreen (Resistive or Capacitive)
 - High Shock & Vibration
 - Low Power Consumption
 - Remote Brightness Control Option
 - Digital controls w/on screen display
- Also available in OEM/Open-Frame Design

The SV-1700LED model is now end of life and has been discontinued. Please contact us for replacement options.



GALLERY IMAGES



PRODUCT DESCRIPTION

Stealth's 17" Sunlight Readable LCD Monitor is designed to operate in extreme ambient light conditions. Stealth's high bright monitors outperform commercially available products that wash out in direct and indirect sunlight conditions.

The model SV-1700LED-PM-HB is environmentally sealed NEMA 4X / IP66 specifications and features Stainless Steel front panel that is resistant to dust/dirt penetration or even liquid splashes.

This 17" Sunlight Readable Display is rated for 1,000 Nits (Cd/m²) high brightness and comes equipped with adjustable brightness controls. The display can also be configured with Resistive or Capacitive touchscreen. Ideal for inside and outside use in marine, mobile, kiosks, control, security, drilling platforms, outdoor displays, yachts, aircraft or digital sign applications.

Stealth.com has a wide range of industrial LCD products that include; NEMA 4/4X / IP65 Stainless Steel, Panel Mount, Rackmount, Open Frame and custom designed configurations.

ADDITIONAL INFORMATION

Bezel Type	Panel Mount
Screen Size	17.0" (Diagonal)
Aspect Ratio	4:3
Native Resolution	1280 x 1024 (Auto sync from 640 x 480 to 1280 x 1024)
Pixel Pitch	0.294mm x 0.294mm
Response Time	5ms Typical
Type	LCD c/w LED Backlighting
Video Input Connectors	VGA / HD-15 DVI Compliant Digital HDCP (DVI-D)
Viewing Angle	80 (up), 80 (down), 80 (left), 80 (right) - (Viewing angle of LCD panel without touch)
Contrast Ratio	1000:1 (typical)
Luminance (Brightness)	1000 cd/m2 typical at center (1000 Nits)
Viewable Image Size	Horizontal: 13.3" / 337.9 mm, Vertical: 10.6" / 270.4 mm
Video Signal	ANALOG: 0.7 Vp-p/75 Ohms
Sync Signal	Separate Sync Sync on Green Composite Sync (Positive/Negative)
Input	Universal Power Supply (removable) 90-240V, +12VDC@100W
Control Buttons (Rear mounted)	Left (-), Right (+), Up, Down, Auto Adjustment, Brightness Hot key, OK, Power ON/OFF
Controls On-Screen Display	Brightness, Contrast, Auto Adjust, Image Position, Image Adjust, Color Adjust, Display Mode, Language Select, OSM Lockout, OSM Time-out
Environmental Rating	Standard Stainless Steel Bezel: NEMA 4X / IP66 Front Panel (when properly installed) corrosion protection, protection against windblown dust and rain, splashing water, and hose-directed water

Panel Finish	Stainless Steel – Brushed #304 (Standard)
Unit Weight	Unit Weight: 18 Lbs (8.16Kg) SV-1700LED-PM-RT-HB-SS-SERIAL – Resistive Touch with Serial/DB9 Interface SV-1700LED-PM-RT-HB-SS-USB – Resistive Touch with USB Interface
Available Models	SV-1700LED-PM-CT-HB-SS-SERIAL – Capacitive Touch with Serial/DB9 Interface SV-1700LED-PM-CT-HB-SS-USB – Capacitive Touch with USB Interface
Dimensions	Panel Mount: 18.94"(W) x 17.0"(H) x 3.1"(D) 481mm x 431.8mm x 78.4mm
Warranty	1 Year Parts & Labor
Disclaimer	Note: Specifications are subject to change without notice.